

96/60291A EP
(anterior 96/60291B EP)



11 Publication number: **0 541 364 A1**

12 **EUROPEAN PATENT APPLICATION**

21 Application number: **92310121.6**

51 Int. Cl.⁵: **G09G 3/36**

22 Date of filing: **05.11.92**

30 Priority: **07.11.91 JP 318622/91**
07.11.91 JP 318623/91
10.12.91 JP 349776/91

43 Date of publication of application:
12.05.93 Bulletin 93/19

84 Designated Contracting States:
DE FR GB

71 Applicant: **CANON KABUSHIKI KAISHA**
30-2, 3-chome, Shimomaruko, Ohta-ku
Tokyo (JP)

72 Inventor: **Kondo, Shigeki, c/o Canon**
Kabushiki Kaisha
30-2 Shimomaruko 3-chome
Ohta-ku, Tokyo (JP)
Inventor: **Sugawa, Shigetoshi, c/o Canon**
Kabushiki Kaisha
30-2 Shimomaruko 3-chome
Ohta-ku, Tokyo (JP)
Inventor: **Kohchi, Tetsunobu, c/o Canon**
Kabushiki Kaisha
30-2 Shimomaruko 3-chome
Ohta-ku, Tokyo (JP)


74 Representative: **Beresford, Keith Denis Lewis**
et al
BERESFORD & Co. 2-5 Warwick Court High
Holborn
London WC1R 5DJ (GB)

54 **Liquid crystal device and driving method therefor.**

57 A liquid crystal device of active matrix type including a layer of a liquid crystal material and a plurality of unit cells each provided with an active element, comprises:

a circuit for maintaining signal lines, for supplying signals for determining the optical state of the liquid crystal material, at a reference potential during a period, other than a period in which the signals are supplied to the unit cells.

FIG. 8



EP 0 541 364 A1

Jouve, 18, rue Saint-Denis, 75001 PARIS

BACKGROUND OF THE INVENTIONField of the Invention

5 The present invention relates to a liquid crystal device adapted for use in an image information processing apparatus such as a flat panel display, a projection television or a video recorder, or the like, and a driving method therefor.

Related Background Art

10 Liquid crystal devices, particularly so-called active matrix liquid crystal display devices employing active elements as the pixel switches, have been widely utilized, principally employing twisted nematic (TN) liquid crystal, and commercialized in the fields of flat panel displays and projection televisions. The above-mentioned active matrix element, represented by a thin film transistor (TFT), a thin film diode and an MIM (metal-insulator-metal) element is used for assisting the optical switching response of liquid crystal by maintaining a voltage application state for a period longer than the actual line selecting period for the TN liquid crystal of a relatively slow response, and realizing a practical memory state for a frame period, by the above-mentioned voltage application state, in liquid crystal lacking the memory property (self-holding property) such as the TN liquid crystal mentioned above. Also the configuration utilizing such active matrix elements is in principle free from crosstalk among the lines or the pixels, thus providing satisfactory display characteristics.

20 In recent years there has been developed ferroelectric liquid crystal (FLC) with a response speed which is several orders higher than that of the TN liquid crystal, and the developments of a display panel, a light valve etc. utilizing such FLC have been announced. There is conceived possibility of obtaining a further improved display device by driving the FLC with the above-mentioned active matrix elements, and the combination of FLC and the above-mentioned TFT is already disclosed for example in the U.S. Patent No. 4,840,462 and in the Proceedings of the SID, vol. 30, 1989 "Ferroelectric Liquid-Crystal Video Display".

Fig. 1 is a circuit diagram of such conventional active matrix liquid crystal device.

25 The driving unit of said device is composed of pixels parts each consisting of a liquid crystal cell 701, containing liquid crystal sealed between a common electrode (with a potential V_{COM}) and an individual pixel electrode, and pixel TFT's 702; an image signal line parts (hereinafter called signal lines 703); a line buffer 704; a shift pulse switch 708; a horizontal shift register 705; gate signal lines (hereinafter called gate lines) 711; and a vertical shift register 706, and the recording signals are transferred from an input terminal 707 to the successive pixels or successive lines in successive timings.

30 Fig. 2 is a timing chart showing the driving pulses for said conventional active matrix liquid crystal device, in a line-sequential drive. The image signal S_{Vi} to be recorded on the liquid crystal is stored, by an amount corresponding to a line, in the buffer 704, through the shift pulse switch 708 which is controlled by the output signal, of a frequency synchronized with said image signal, from the horizontal shift register 705. After the storage of the image signal of all the pixels of an n-th line is stored in the line buffer 704, the pixel image signals V_{PEN} are recorded in the liquid crystal cells 701 of said line, through an output switch 701, turned on by a signal ϕ_T , of the line buffer 704 and pixel switches 702 turned on by signals S_2 from the vertical shift register 706. The signal transfer to the liquid crystal cells is conducted collectively for a line, generally during a blanking period in a horizontal scanning period. According to the above-explained timings, the pixel image signals V_{PEN} , V_{PEN+1}, \dots are recorded in the successive lines.

35 The signal voltage thus transferred causes the movement of liquid crystal molecules constituting each cell, thereby causing a change in the transmittance of the liquid crystal cell, depending on the directions of polarizing plates so positioned as to constitute a cross polarizer, as shown in Fig. 3.

40 The signal voltage V_{SIG} shown on the abscissa in Fig. 3 is known to have different meanings according to the liquid crystal to be employed. For example, in case of TN liquid crystal, this value is defined as the effective voltage V_{rms} . Fig. 4A provides qualitative explanation on this value. The polarity of the signal voltage is alternated in every frame, in order to avoid the prolonged application of a DC signal to the liquid crystal, but the liquid crystal itself responds to the AC voltage component, represented by hatched areas. Consequently, the effective voltage V_{rms} is represented by the following equation (1):

$$V_{rms} = \sqrt{\frac{1}{t_F} \int_0^{t_F} (V_{LC}(t) - V_{COM})^2 dt} \quad (1)$$

wherein t_F is the time of two frames and $V_{LC}(t)$ is the signal voltage transferred to the liquid crystal.

On the other hand, the above-mentioned FLC is generally driven with a DC voltage. In case of bistable FLC (for example chiral smectic liquid crystal, preferably of a chiral smectic phase C (SmC*) or phase H (SmH*), or of SmI*, SmF* or SmG*), there is employed a driving wave form as shown in Fig. 4B. More specifically, the signal voltage $V_{LC}(t)$ at first resets the liquid crystal to one of the bistable states by V_R , and then applies a writing voltage signal V_W . The signal voltage V_{SIG} contributing to the transmittance shown in Fig. 3 is again represented by hatched areas. Different from the case of TN liquid crystal, the DC component of the writing voltage constitutes directly the signal voltage V_{SIG} .

However, in such conventional configuration, the signal voltage accumulated in the liquid crystal cell, through the signal transfer in the aforementioned timings, is known to fluctuate principally for the following two reasons.

The first reason lies in the swing of the liquid crystal voltage, resulting from a voltage variation in the gate line 711 for driving each pixel switch. The swing ΔV_{LC1} in the liquid crystal voltage can be represented by the following equation (2):

$$\Delta V_{LC1} = \frac{C_{GD}}{C_{GD} + C_{LC}} \cdot \Delta V_G \quad (2)$$

wherein C_{LC} is the capacitance of the liquid crystal cell, C_{GD} is the gate-drain capacitance of the pixel TFT 702, and ΔV_G is the voltage variation of the gate line 711 (amplitude of gate voltage required for on-off operation of the pixel TFT).

The second reason lies in the swing of the liquid crystal voltage, caused by a voltage variation in the signal line 703 for transferring the image signal $V_{LC}(t)$ to the liquid crystal cells. Said swing ΔV_{LC2} in the liquid crystal voltage can be represented by the following equation (3):

$$\Delta V_{LC2} = \frac{C_{DS}}{C_{DS} + C_{LC}} \cdot \Delta V_S \quad (3)$$

wherein C_{LC} is the capacitance of the liquid crystal cell, C_{DS} is the parasite capacitance between each pixel electrode and the signal line, and ΔV_S is the voltage variation in the signal line 703 (namely the image signal voltage for each line or each pixel).

Fig. 5 shows the first-mentioned swing ΔV_{LC1} of the liquid crystal voltage resulting from the voltage variation in the gate line 711, while Figs. 6 and 7 show the second-mentioned swing ΔV_{LC2} of the liquid crystal voltage resulting from the voltage variation in the signal line.

As will be apparent from Fig. 5, the voltage swing ΔV_{LC1} caused by the first reason always varies the voltage applied to the liquid crystal cell to the negative side. Consequently, said voltage change ΔV_{LC1} generates a state equivalent to the continuous application of a DC voltage component, and said DC voltage component leads to the coagulation of liquid crystal molecules particularly when the TN liquid crystal is employed. Also in the foregoing equation (2), if the capacitance C_{GD} fluctuates for example by the instability in the process, the voltage swing ΔV_{LC1} itself also fluctuates. In case of display with gradation by a liquid crystal display device, the gradation characteristics are lost if said fluctuation exceeds the voltage range required for the display of one level (ca. 47 mV for a level for displaying 64 levels within an amplitude of 3 V).

Certain proposals have been made for coping with said voltage variation ΔV_{LC1} , particularly for removing the DC voltage component. A widely employed method consists, in case of using the TN liquid crystal, of providing an auxiliary capacitance parallel to the capacitance of the liquid crystal, thereby increasing the apparent cell capacitance to increase the denominator in the equation (2), thus reducing the swing. Another proposal consists of providing each pixel with plural TFT's and specially designing the arrangement thereof, thereby rendering the swing less conspicuous. Also for reducing the fluctuation in the swing, there has been tried to suppress the fluctuation in the parasite capacitance among the elements, by varying the structure of the pixel TFT from the conventional inverse staggered TFT of amorphous silicon to a planar TFT employing polysilicon, and introducing the ion implantation, utilized in the IC process, into the formation of source and drain of the TFT.

On the other hand, based on the voltage variation ΔV_{LC2} of the second reason, when a signal voltage is supplied to a pixel and a charge is accumulated in the liquid crystal cell, the signal charge of said pixel varies

according to the equation (3) if a signal is transferred to another pixel through the same signal line. In the above-explained circuit configuration, the signal line 703 for signal transfer has a certain parasite capacitance C_S which in practice is several hundred times to several thousand times larger than the liquid crystal capacitance of the pixel. In the transfer of a signal voltage from the buffer to the liquid crystal cell in such system, the signal voltage accumulated in said parasite capacitance is scarcely attenuated, and the voltage of the signal line can be considered to be always fixed at the signal voltage then transferred. When a new signal voltage is subsequently supplied for transfer to another pixel, the voltage of the signal line varies for the same reason. The drawbacks induced by such voltage variation will be considered more detailedly in the following.

For the purpose of simplicity, it is assumed that, in the entire image frame, a certain horizontal line only displays black (absolute signal level being minimum) while other lines display white (absolute signal level being maximum). In such situation, the signal level of the black-displaying line swings according to the equation (3), at the signal transfers to other lines, and such situation is illustrated in Figs. 6 and 7. Fig. 6 shows the drawback induced by the voltage variation ΔV_{LC2} of the second reason, in case of FLC, and Fig. 7 shows the drawback in case of TN liquid crystal.

Fig. 7 shows a case in which an n -th line in the input image signal V_{IN} displays black while other lines display white. As will be apparent from Fig. 7, the image signal V_{LCn} of the n -th line is subjected to a variation of the signal level by ΔV_{LC2} according to the foregoing equation (3), whereby the effective voltage V_{rms} represented by the equation (1) varies, thus becoming unable to maintain the black level. More specifically, the equation (1) is changed to the following equation (4), whereby the effective voltage V_{rms} varies:

$$V_{rms} = \sqrt{\frac{1}{t_F} \int_0^{t_F} (V_{LC}(t) - \Delta V_{LC2} - V_{COM})^2 dt} \quad (4)$$

Fig. 6 shows that, in case of FLC, the voltage V_{LCn} written in a pixel in the n -th line varies by the subsequent write-in of the pixel image signals by gate signals $S2_{n+1}$, $S2_{n+2}$, $S2_{n+3}$,... of another line. Consequently the display level of said line gradually varies to another level by the voltage variation ΔV_{LC2} according to the equation (3), thus becoming unable to maintain the original display level.

This phenomenon can be numerically analyzed in the following manner.

As an example, there are employed a signal line 703 of Al (aluminum) with a width of $3 \mu m$ and a thickness of $0.5 \mu m$; a pixel electrode of a size of $30 \times 30 \mu m$ or $150 \times 150 \mu m$; a liquid crystal cell gap of $6 \mu m$; a dielectric constant of liquid crystal of 5.0; an interlayer insulation film between the signal line and the gate line with a dielectric constant of 3.9 and a thickness of $0.5 \mu m$; a distance between the signal line and the pixel electrode of $3 \mu m$; and a driving voltage of $\pm 5.0 V$ at maximum for the liquid crystal. In such system, by calculating the parasite capacitance C_{DS} and the liquid crystal cell capacitance C_{LC} and substituting these values into the equation (3), there is obtained a variation in the pixel voltage as represented by the following equation (5), for a pixel size of $150 \times 150 \mu m$:

$$\Delta V_{LC2} = \frac{C_{DS} \times V_S}{C_{DS} + C_{LC}} = \frac{1.37E-14 \times 10}{1.37E-14 + 1.66E-13} = 0.76[V] \quad (5)$$

In case of effective voltage drive as in the TN liquid crystal, the effective voltage V_{rms} varies according to the foregoing equation (4), and, in the case of DC voltage drive as in the FLC, said voltage variation is directly reflected in the variation of the signal voltage for the liquid crystal.

Such voltage variation is more complex in case the signal level varies linearly as in the ordinary television image signal. In any case, the signal level of a pixel varies at the signal transfer to another pixel, if the level of said signal is different from that of the first-mentioned pixel. As said variation occurs in a direction to approach the signal level of said another pixel, the image appears to blot between the pixels or between the lines, and the image boundary becomes less clear. Such blotting appears as vertically streaking smears on the image, thus significantly deteriorating the image quality.

Also for a pixel size of $30 \times 30 \mu m$, there is obtained the result shown by the equation (6) in the above-mentioned black-and-white display. It will thus be understood that the voltage variation ΔV_{LC2} of the second reason becomes unnegligibly large, as the pixel size becomes smaller and the resolving power of the display device becomes higher:

$$\Delta V_{LC2} = \frac{C_{DS} \times V_S}{C_{DS} + C_{LC}} = \frac{2.75E-15 \times 5}{2.75E-15 + 6.64E-15} = 1.47[V] \quad (6)$$

This is because the decrease in the parasite capacitance C_{DS} between the signal line and each pixel electrode

at the reduction of pixel size is less than that in the liquid crystal capacitance C_{LC} , so that the influence of C_{DS} becomes more conspicuous by the reduction in the liquid crystal capacitance C_{LC} .

In order to cancel the voltage variation ΔV_{LC2} of the second reason, there is conceived to reduce C_{DS} to zero, but this is absolutely impossible as long as the above-explained circuit configuration is adopted, regardless how finely it is made. Nextly conceivable is the reduction of the voltage variation in the signal line, and, for this purpose, there is required to reduce the proportion of the parasite capacitance of the signal line with respect to the entire capacitance. However, the parasite capacitance of the signal line, though being reducible to a certain extent by the reduction of the width of the line, will still be far larger (still several hundred times to several thousand times) than the capacitances C_{DS} , C_{LC} at the liquid crystal side. Also the capacitance C_{DS} cannot be made larger, as it is mostly determined by the structure and size of the pixel part.

Consequently, there is nextly conceived as the increase of the liquid crystal capacitance C_{LC} . For this purpose it is conceivable to form, as in the current TN liquid crystal cell configuration, to form a large auxiliary capacitance, parallel to the liquid crystal capacitance C_{LC} . However, in order to cancel the influence of the capacitance C_S of several hundred times to several thousand times, it is required to attach an auxiliary capacitance of a similar or larger magnitude, and the addition of such large auxiliary capacitance increases the load of signal transfer to the pixel parts. Such capacitance cannot be increased excessively since the increase in the number of pixels reduces the time allotted to each line.

In summary, the drawbacks associated with the voltage variation ΔV_{LC2} of the second reason will become more conspicuous in the display devices requiring high definition and high-speed drive, such as the display for the high definition television which is expected to become rapidly popular in the future.

On the other hand, the status of the display device employing liquid crystal with memory property is as follows. In such case, the optical axis of liquid crystal and that of the polarizing plates are so aligned that one of two optical bistable states provides black display while the other provides black display. A voltage providing the white display is called an optical information recording signal, while a voltage providing the black display is called a reset signal. In case of driving the FLC with bistable states, each pixel has to be given, prior to the access to the recording signal, a black (reset) signal in order to reset the record at the preceding access.

In practice, however, the parasite capacitance C_S is several hundred times to several thousand times larger than the liquid crystal capacitance in the pixel part, and is about equal to or even larger than the capacitance in the buffer. Thus the signal voltage (optical information recording signal or reset signal) entered from the input terminal 707 is transferred while charging and discharging the capacitance of the buffer and the parasite capacitance of the line, whereby the signal transferring ability of the device is deteriorated, also under influence of the resistance in the lines. Besides, these phenomena become more conspicuous as the display becomes larger in size and higher in definition.

Furthermore, the conventional driving method has been associated with the following drawbacks.

In the driving method shown in Fig. 7, the voltage of the pixel electrode, though variable depending on the signal voltage, is always positive with respect to the potential of the common electrode, and such situation is equivalent to the continuous application of a DC voltage component to the liquid crystal cell. Such DC component leads to the coagulation of the liquid crystal molecules, particularly in case of the TN liquid crystal.

Certain proposals have been made for eliminating said DC voltage component. Already employed widely is the frame inversion driving method shown in Fig. 4A. In this driving method, the polarity of the signal voltage with respect to the common electrode potential V_{COM} is inverted every frame in such a manner that an N-th signal voltage is applied positively with respect to the potential of the common electrode while an (N+1)-th signal voltage is applied negatively, whereby the DC voltage component applied to the liquid crystal cell is cancelled and the coagulation of the liquid crystal molecules is prevented.

There have also been proposed driving methods with inversion in every horizontal scanning period or in every pixel, for attaining similar effects. However, such methods are still associated with the following drawbacks.

With a signal voltage V_N applied to the pixel electrode at the N-th time and a signal voltage $-V_{N+1}$ applied at the (N+1)-th time, a bias ($V_N + V_{N+1}$) is applied between the source and the drain of the pixel TFT 102 at the signal application of the (N+1)-th time. Thus, in the above-explained inversion driving method with a maximum amplitude V_{MAX} of the signal voltage, there is applied a bias of $2V_{MAX}$ at maximum between the source and the drain of the pixel TFT 102, which is therefore required to have an on-state source-drain voltage resistance exceeding said maximum bias.

Such requirement can be alleviated by a reduction in the maximum amplitude of the signal voltage, but such method is undesirable because it tends to sacrifice the display of gradation as will be understood from Fig. 3, whereas the display devices require an improved definition in the future, as in those for the high definition television which is expected to become rapidly popular.

Another method for alleviating said voltage resistance requirement lies in the use of a MOS transistor of

a high voltage resistance structure, such as the LDD (lightly doped drain) structure, as the pixel switch 102. However, the MOS transistor of currently proposed structure for high voltage resistance is associated with a drawback of a loss in gm because of an increased serial resistance to the source and the drain, as a trade-off for the improvement in the voltage resistance. As explained above, high-speed drive will be increasingly required for the liquid crystal devices, as in those for high-definition television, and a larger gm will be required for this purpose in the pixel switching TFT. Besides, the MOS transistor of the above-mentioned high voltage resistance structure is inevitably associated with a high manufacturing cost, because of the complex manufacturing process.

Such drawbacks are not limited to the case of TN liquid crystal, but also are present in case of driving FLC by active matrix elements, utilizing a signal as shown in Fig. 4B.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a liquid crystal device of a high definition, capable of driving a unit liquid crystal cell with a high speed, and a driving method therefor.

Another object of the present invention is to provide a liquid crystal device capable of preventing the undesirable influence of the parasite capacitance on the resetting operation, and a driving method therefor.

Still another object of the present invention is to provide a liquid crystal device enabling drive of a higher speed than in the conventional configuration, even with the use of an active element of a simple structure as the pixel switch, and a driving method therefor.

Still another object of the present invention is to provide a liquid crystal device capable of variation in the information signal voltage applied to the unit cell, and a driving method therefor.

The above-mentioned objects can be attained, according to the present invention, by a liquid crystal device of active matrix type provided with a layer of a liquid crystal material and a plurality of unit cells each including an active element, comprising a circuit for maintaining a signal line, for supplying signals for determining the optical state of the liquid crystal material, at a reference potential in a period, excluding a period in which said signals are supplied to said unit cells.

Also the above-mentioned objects can be attained, according to the present invention, by a liquid crystal device of active matrix type provided with a layer of a liquid crystal material and a plurality of unit cells each including an active element, comprising a circuit which supplies said unit cells with time-sequential signals for determining the optical state of the liquid crystal and which maintains said unit cells at a reference potential after the supply of a first signal to said unit cells but prior to the supply thereto of a second signal succeeding to said first signal.

Also the above-mentioned objects can be attained, according to the present invention, by a liquid crystal device of active matrix type provided with a layer of a liquid crystal material having at least two stable states, and a plurality of unit cells each including an active element, comprising:

a circuit for supplying said unit cells with time-sequential signals for determining the optical state of the liquid crystal material through a common signal line;

a circuit for maintaining said unit cells at a reference potential after the supply of a first signal of said time-sequential signals to said unit cells but prior to the supply thereto of a second signal succeeding to said first signal;

wherein a reference voltage supplying line, for supplying the reference voltage for maintaining said unit cells at the reference potential, is provided separately from said common signal line.

Also the above-mentioned objects can be attained, according to the present invention, by a driving method for a liquid crystal device of active matrix type provided with a layer of a liquid crystal material and a plurality of unit cells each including an active element, comprising a step of maintaining a signal line, for supplying signals for determining the optical state of the liquid crystal material, at a reference potential in a period excluding a period in which said signals are supplied to said unit cells.

Also the above-mentioned objects can be attained, according to the present invention, by a driving method for a liquid crystal device of active matrix type, provided with a layer of a liquid crystal material and a plurality of unit cells each including an active element, comprising a step of maintaining said unit cells at a reference potential after the supply of a first signal, in time-sequential signals for determining the optical state of the liquid crystal material, to said unit cells but prior to the supply thereto of a second signal succeeding to said first signal in said time-sequential signals.

Also the above-mentioned objects can be attained, according to the present invention, by a driving method for a liquid crystal device of active matrix type, provided with a layer of a liquid crystal material having at least two stable states, and a plurality of unit cells each including an active element, comprising steps of:

supplying time-sequential signals, for determining the optical state of the liquid crystal material, from

a common signal line to said units cells; and

connecting said units cells to a reference voltage supply line which is separate from said common signal line, thereby maintaining said unit cells at a reference potential, after the supply of a first signal in said time-sequential signals to said unit cells but prior to the supply thereto of a second signal succeeding to said first signal.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a circuit diagram of a conventional active matrix liquid crystal display device;

Fig. 2 is a timing chart showing the driving method for the device shown in Fig. 1;

Fig. 3 is a chart showing the relationship Between the transmittance and the signal voltage in a liquid crystal display device;

Figs. 4A and 4B are timing charts showing an example of the conventional driving signal;

Figs. 5 and 6 are timing charts for explaining the variation in the voltage applied to the pixels in conventional liquid crystal display devices;

Fig. 7 is a timing chart showing another example of the conventional driving signal;

Fig. 8 is a circuit diagram of a liquid crystal display device constituting embodiments 1, 2 and 4 of the present invention;

Fig. 9 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 1;

Fig. 10 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 1;

Fig. 11 is a circuit diagram of a liquid crystal display device constituting an embodiment 3 of the present invention;

Fig. 12 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 3;

Fig. 13 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 4;

Fig. 14 is a circuit diagram of a liquid crystal display device constituting an embodiment 5 of the present invention;

Fig. 15 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 5;

Fig. 16 is a circuit diagram of a liquid crystal display device constituting embodiments 6 to 8 of the present invention;

Fig. 17 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 6;

Fig. 18 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 7;

Fig. 19 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 8;

Fig. 20 is a circuit diagram of a liquid crystal display device constituting embodiments 9 and 10 of the present invention;

Fig. 21 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 9;

Fig. 22 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 10;

Fig. 23 is a circuit diagram of a liquid crystal display device constituting an embodiment 11 of the present invention;

Fig. 24 is a timing chart for explaining the driving method for the liquid crystal display device of the embodiment 11;

Fig. 25 is a schematic view of a liquid crystal device of the present invention; and

Fig. 26 schematically shows a liquid crystal element.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The liquid crystal material employed in the present invention may have a stable state, or at least two stable states. The former is represented by nematic liquid crystals, such as twisted nematic liquid crystal or super twisted nematic liquid crystal. The latter is represented by ferroelectric liquid crystals, preferably chiral smectic

liquid crystals. Specific examples of such liquid crystal includes those of chiral smectic phase C (SmC^*), SmH^* , SmI^* , SmF^* and SmG^* .

Also the means for supplying the reference voltage, for maintaining the unit cells or the signal lines at the reference potential can be a bus line (power supply line) for supplying said voltage from an external power source, or a reference voltage source provided in an integrated semiconductor circuit for generating the reference voltage by dropping a voltage supplied from an external power source and a line connected thereto.

[Embodiment 1]

Fig. 8 is a diagram of a driving circuit of an active matrix liquid crystal device constituting an embodiment of the present invention.

There are shown a capacitance 101 corresponding to a liquid crystal cell; a pixel TFT 102 serving as a selector switch for applying a signal voltage to the liquid crystal cell 101; a signal line 103; a transfer gate 104; a buffer capacitance 105; a switching TFT 106 for accumulating an external signal pulse in the corresponding buffer capacitance 105; a horizontal shift register 107 for releasing, in succession, selection signals for pulse driving of the switching TFT's 106; and a vertical shift register 108 for releasing, in succession, selection signals for driving the pixel TFT's 102.

The driving circuit is further provided with a holding signal line 109 connected to a bias source for fixing the voltage of the signal lines and serving to maintain the signal lines 103 at a constant voltage; and switching TFT's 110 for selectively connecting the recording signal lines 103 with the holding signal line 109.

In the following there will be explained the functions of this circuit in case of line-sequential drive of an active matrix device employing the TN liquid crystal.

In the above-explained circuit configuration, when the image signals S_{Vi} of a line are entered in succession from an input terminal 111, the horizontal shift register 107 driven by the pulses synchronized with the frequency of said image signals turns on the switching TFT's 106 in succession, whereby the image signals of the pixels of said line are transferred in succession to the buffer capacitances 105. Then, in so-called blanking period which is after the signal transfer to the buffer capacitance 105 of the last bit in said line but prior to the entry of the image signals of a next line into the input terminal 111, the transfer gates 104 and the pixel TFT's 102 are simultaneously turned on whereby said image signals are transferred to the liquid crystal cells 101 of the pixels of said line. In fact said signal transfer to the pixels is executed within a part of the blanking period, and the remaining part is used for an operation for maintaining the signal line 103 at a constant voltage.

Said operation is achieved by turning on the switching TFT's 110, after the transfer gates 104 and the pixel TFT's 102 are turned off. Said switching TFT's 110 are turned on for a period enough for charging the parasite capacitances associated with the signal lines 103, and are turned off prior to the end of the blanking period. As a result, the signal lines 103 are maintained at a voltage determined by the holding signal line 109, until the next transfer of image signals, namely until the start of the blanking period of the next horizontal scanning period.

For example, in the image signals for the high-definition television, the horizontal scanning period is about 29 $\mu\text{sec.}$, including a blanking period of about 3 $\mu\text{sec.}$ Consequently the turn-on period of the transfer gates 104 and the pixel TFT's 102 for the transfer of the image signals to the pixels and that of the switching TFT's 110 for maintaining the signal lines 103 at the constant voltage will be about 1 $\mu\text{sec.}$ each. Therefore, the signal line 103 is set at the voltage of the image signal for a period of 1/29 of the horizontal scanning period, but is maintained at the constant voltage for the remaining part, namely 28/29 of the horizontal scanning period. By repeating such operation, the voltage V_s of the signal line 103 is maintained at a constant value for most of the entire display period, despite of the variation in the image signal voltage.

Fig. 9 shows the timings of the above-explained operations. In Fig. 9 there are shown the image signals S_{Vi} for the N-th and (N+1)-th lines; gate input signals ϕ_T and $\phi_{Vi} - \phi_{Vn}$ respectively of the transfer gates 104 and the pixel TFT's 102; a gate input signal S3 for the switching TFT's 110; signal voltages V_{PEN} , V_{PEN+1} respectively of the pixels of the N-th and (N+1)-th lines; and the voltage V_s of the signal lines 103. As will be apparent from this chart, the voltage V_s of the signal lines is always maintained at a constant value V_{RES} , only except for a part of the blanking period T_B .

With the above-explained timings, the potential V_s of the signal lines 103 only varies for a period of about 1 $\mu\text{sec.}$ at longest, and the liquid crystal molecules do not respond to such voltage variation within such short period. Consequently, the voltage of the signal lines 103 which has to be taken into consideration for the liquid crystal molecules is the constant voltage V_{RES} supplied constantly by the holding signal line 109. When the voltage variation ΔV_s in the signal lines 103 becomes constant, the voltage variation ΔV_{CL2} in the liquid crystal capacitance 101 where the pixel TFT 102 is turned off is always constant, according to the foregoing equation (3). The effective voltage V_{rms} actually applied to the liquid crystal in such state is represented by the following

equation (7):

$$V_{rms} = \sqrt{\frac{1}{t_F} \int_0^{t_F} (V_{LC}(t) - \Delta V_{LC2} - V_{COM})^2 dt} \quad (7)$$

In contrast to the conventional configuration in which, even for a given V_{LC} , the effective voltage V_{rms} always varies depending on the values of other pixel signals, the effective voltage V_{rms} in the present embodiment is always uniquely determined by the given signal voltage V_{LC} . Consequently the curve showing the relation between the transmittance and the effective voltage V_{rms} is aberrated by the contribution of ΔV_{LC2} , but a one-to-one correspondence is established therebetween. Thus the characteristics of the display device may be determined from thus aberrated curve. Otherwise, a display device of the originally designed characteristics without said aberration may also be obtained by regulating the signal voltage V_{LC} , as will be apparent from the equation (7).

It is therefore rendered possible to avoid the vertically streaking smears, resulting from the swing of the signal voltage in each pixel, induced by the signals to other pixels connected to a same signal line 103, whereby the image quality is improved.

As an example, in the signal timings of the above-explained example, by setting the original signal voltage in a liquid crystal capacitance 101 as 0 V and setting the holding voltage V_{RES} of the signal line 103 as 0 V, said liquid crystal capacitance is maintained at 0 V until the application of a next signal voltage of another value.

Also in said example, by selecting the holding voltage at a value not equal to the signal voltage (= 0 V) of the considered liquid crystal capacity 101, for example at the center value (= 2.5 V) of the maximum (= 5 V) and minimum (= 0 V) of the signal voltage, the variation ΔV_{LC2} in the signal voltage of the liquid crystal capacitance 101 for a cell of a size of 150 μ is given by the following equation (8):

$$\Delta V_{LC2} = \frac{C_{DS} \times V_S}{C_{DS} + C_{LC}} = \frac{1.37E-14 \times 2.5}{1.37E-14 + 1.66E-13} = 0.19[V] \quad (8)$$

Also in case the holding voltage is selected at the maximum value (= 5 V) of the signal voltage, there is obtained a value represented by the following equation (9):

$$\Delta V_{LC2} = \frac{C_{DS} \times V_S}{C_{DS} + C_{LC}} = \frac{1.37E-14 \times 5}{1.37E-14 + 1.66E-13} = 0.38[V] \quad (9)$$

Consequently the display device can be designed in advance, in consideration of these variations ΔV_{LC2} in the signal voltage. Otherwise, since said variation ΔV_{LC2} is constant, regardless of the signal voltages in other pixels, the original signal voltage may be altered so as to cancel said variation ΔV_{LC2} . For example, in order to obtain a pixel signal voltage of 0 V when the holding voltage is selected as 2.5 V, the original signal voltage should be selected as -0.20 V. Also in order to obtain a pixel signal voltage of 0 V when the holding voltage is selected as 5 V, the original signal voltage should be selected as -0.4 V. Stated differently, the original voltage V_{LC} should be selected in such a manner that the effective voltage V_{rms} in the equation (1) becomes equal to that in the equation (4).

As will be apparent from the foregoing discussion, the signal voltage of each pixel is no longer influenced by that of other pixels by mere setting that ΔV_{LC2} becomes constant, and the performances of the display device can therefore be improved. Particularly the vertically streaking smear is almost completely eliminated.

As an example, in a display of the NTSC image signal on a liquid crystal panel employing the driving circuit of the present embodiment and containing 360 x 480 pixels (x 3, for R, G, B) with a holding voltage of 0 V, the blotting phenomenon of pixels in the vertical direction was not observed at all. In this display, there was employed the frame inversion drive in which the polarity of the signal voltage was inverted every frame, with a driving voltage of $\pm 5 - 0$ V, and the input image signal was corrected in advance according to the foregoing equation (7).

Also in a similar drive with a driving voltage of $\pm 8 - 0$ V and without the correction according to the equation (7), no significant difference from the above-mentioned case could be observed, except for an increased amplitude of the driving voltage.

Furthermore, similar effects could be obtained in cases with a driving voltage of $\pm 5 - 0$ V, a holding voltage V_{RES} of 2.5 V or 5 V and with the correction according to the equation (7).

[Embodiment 2]

Fig. 10 shows the timing of functions in a driving circuit constituting an embodiment 2 of the present invention. The configuration of the driving circuit is same as that in the embodiment 1, and the transfer of the image signals to the pixels is executed utilizing a part of the blanking period as explained before. However, the difference from the embodiment 1 lies in a fact that the operation of maintaining the signal lines 103 at a constant value is executed not only in the blanking period but also in a horizontal scanning period. More specifically, after the transfer gates 104 and the pixel TFT's 102 are turned off, the switching TFT's 110 are turned on, and then turned off at least after a time enough for charging the parasite capacitances associated with the signal lines 103 but prior to the transfer of the signals of a next line to the pixels.

When a liquid crystal panel, same as in the embodiment 1, was driven with the above-explained method, under similar conditions with a driving voltage of $\pm 5 - 0$ V, a holding voltage of 0 V and with correction for the input signal, there could be attained similar effects.

[Embodiment 3]

Fig. 11 shows a driving circuit for a sequential-drive active matrix liquid crystal device, constituting an embodiment 3 of the present invention. In contrast to the line-sequential drive for every horizontal line employed in the embodiment 1, the present embodiment employs a pixel-sequential drive.

In this driving circuit, the signal voltages are directly supplied, in succession, to the liquid crystal cells 101, without employing the transfer gates 104 and the buffer capacitances 105 shown in Fig. 8, and a second horizontal shift register 312 is provided for driving the switching TFT's 110 in succession, according to the timings of said supply.

In the above-explained circuit configuration, when the image signals S_{Vi} of a line are entered in succession from the input terminal 111, the image signals of the pixels of said line are transferred, in succession, to all the pixels of said horizontal line, through switching TFT's 106 which are turned on by the first horizontal shift register driven by the pulses synchronized with the frequency of said image signals, and through the pixel TFT's turned on by the vertical shift register 108. The TFT's 106, 102 which have been turned on for the signal transfer are turned off after said signal transfer, and the switching TFT's 110 are instead turned on by the second shift register 312, whereby all the vertical signal lines 103 are maintained at a constant holding voltage. For example, in case of NTSC television image signal, a horizontal scanning period is about 63 μ sec., and, if a horizontal scanning line contains 480 pixels, the signal pulse width per pixel is about 100 nsec. Consequently the signal line 103 is maintained at the image signal voltage for a period of 1/630 of the horizontal scanning period, but is maintained for the remaining period of 629/630 at the constant voltage. By the repetition of such operation, the voltage of the signal line 103 is maintained at a constant voltage for most of the entire display period, despite of the variation in the image signal voltage.

Fig. 12 shows the timings of the above-explained operations. In Fig. 12 there are shown the image signals S_{Vi} for the N-th and (N+1)-th lines; gate input signals $\phi_{Vi} - \phi_{Vn}$ for the pixel TFT's 102; gate input signals $\phi_{HRL} - \phi_{HRn}$ of the switching TFT's 110; signal voltages V_{PEN} , V_{PIN+1} respectively for the pixels of the N-th and (N+1)-th lines; and voltage V_S of the signal lines 103. As will be apparent from this chart, the voltage V_S of the signal lines is always maintained at a constant value, only except for a part of the horizontal scanning period.

For reasons similar to those explained in the embodiment 1, the signal voltage of each pixel is no longer influenced by those of other pixels, and there can be attained improvements in the performances of the display device, particularly the prevention of vertically streaking smear.

When a liquid crystal panel, similar to that in the embodiment 1, was driven with the driving circuit and method of the present embodiment, under similar conditions with a driving voltage of $\pm 5 - 0$ V, a holding voltage of 0 V and with correction for the input signals, there could be attained similar effects.

[Embodiment 4]

In the foregoing embodiments 1 to 3, the TFT's 110 of the pixels are turned off when the signal lines are maintained at the constant voltage. In contrast, the present embodiment provides a driving method of maintaining the signal lines 103 at the constant voltage while the TFT's of the pixels are turned on. For example, in case of using a liquid crystal material with memory property such as the FLC explained before, it is necessary to reset the preceding signal, governing the optical state, prior to the writing of a new signal voltage. Said liquid crystal resetting signal is normally selected at a same signal level for all the pixels. Consequently, the voltage of said liquid crystal resetting signal may also be utilized as the holding voltage for the signal lines.

This driving method can also be executed in the driving circuit shown in Fig. 8, and is different from the

methods in the embodiments 1 to 3, in that the TFT's 102 (signals $\phi_{V1} - \phi_{Vn}$) of the pixels are turned on twice at the transfer of the image signals and at the transfer of the holding voltage (resetting signal).

Fig. 13 shows the timings of operations of the present embodiment. As will be apparent from this chart, the voltage V_S of the signal lines are always maintained at a constant voltage, except for a part of the blanking period.

As an example, in a display of the NTSC image signal on a liquid crystal panel employing the driving circuit shown in Fig. 8 and containing 360 x 480 pixels (x 3, for R, G and B) with a holding voltage (liquid crystal cell resetting voltage) of -7 V, the blotting phenomenon of pixels in the vertical direction was not observed at all. In said display there were employed driving voltages of +7 - 0 V for image display and -7 V for resetting. The image input signals were corrected in advance, according to the foregoing equation (7).

The access timing, for providing the holding signal immediately before the recording of optical information in each pixel or line, is not limited to those in the foregoing embodiments, but can be suitably selected according to the response of the liquid crystal material to be employed. For example, if the response of the liquid crystal to be employed is slow, the holding signal may be applied to a line in advance by several line scanning periods before the recording of optical information signals in said line, thereby providing an ample response time.

Also the number of pixels or the format of the image signals are not limited to those in the foregoing embodiments, and the present invention is naturally effective in the display devices designed, for example, for the high definition television or the like.

More precisely, even in the present invention, the swing of the signal voltage by the aforementioned second reason appears solely during the period of transfer of the signal voltages to the pixels. Such signal voltage swing in the signal transfer period should also be taken into consideration in case gradation is required in the display device, since such gradation characteristics are destructed if the influence, on the effective voltage, of the sum of said swing in the signal transfer period exceeds one level of said gradation in one frame period. As already explained above, the effective voltage V_{rms} contributing to the drive of TN liquid crystal is represented by the following equation (10):

$$V_{rms} = \sqrt{\frac{1}{t_F} \int_0^{t_F} (V_{LC}(t) - V_{COM})^2 dt} \quad (10)$$

By extending the above-explained concept to a case with a number N of scanning lines, n levels of gradation in the display, a maximum value $V_{rms-MAX}$ and a minimum value $V_{rms-MIN}$ of the effective voltage required for the display with gradation, a signal transfer period t_s , a swing $\Delta V_{LC2}(t)$ in each signal transfer period, and a horizontal scanning period t_H , the signal transfer period t_s has to satisfy the following equation (11):

$$\frac{(N-1) \sqrt{\frac{1}{t_s} \int_0^{t_s} (\Delta V_{LC2}(t) - V_{COM})^2 dt}}{V_{rms-MAX} - V_{rms-MIN}} \leq \frac{1}{n} \quad (11)$$

By solving said equation (11), there can be determined the minimum duty ratio of the horizontal scanning period t_H and the signal transfer period t_s . Said minimum duty ratio should always be taken into consideration even in the exploitation of the present invention.

As an example, there can be considered a system employing signal lines 103 of Al (aluminum) with a width of 3 μm and a thickness of 0.5 μm ; pixel electrodes of a size of 30 x 30 μm or 150 x 150 μm ; a cell gap of 6 μm ; a dielectric constant of liquid crystal of 5.0; an interlayer insulation film between the signal line and the gate line with a dielectric constant of 3.9 and a thickness of 0.5 μm ; a distance of 3 μm between the signal line and the pixel electrode; a maximum liquid crystal driving voltage of ± 5.0 V; and a holding voltage of 0 V. In case of display with 256 levels in such device, said minimum duty ratio is about 75.1 for the liquid crystal cells of 30 x 30 μm and about 38.8 for the liquid crystal cells of 150 x 150 μm .

In the above-explained embodiments 1 to 4, the signal lines are maintained at a constant voltage for the

almost entire period, only excluding the period of supply of the recording signal voltages to the pixels. Thus the recording signal voltage supplied to each pixel is no longer influenced by those supplied to other pixels, whereby the vertically streaking smear can be prevented and there is attained a driving method suitable for display devices requiring high definition and high-speed drive, such as those for the high definition television.

Thus provided is an active matrix liquid crystal display device capable of high-speed drive, which can be utilized for a flat display for direct observation or a projection display, with a high definition. It is also possible to obtain a flat color television or a projection television of a high definition, in reflective or transmissive type, by providing the respective pixels with color filters or by employing a plurality of the liquid crystal devices employing the driving method or driving circuitry of the present invention and illuminating said devices with colored lights.

[Embodiment 5]

In the following there will be detailedly explained an embodiment 5 of the present invention, with reference to the attached drawings.

Fig. 14 is a circuit diagram of the driving circuit of an active matrix liquid crystal device constituting the embodiment 5 of the present invention, wherein shown are a capacitance 101 of a liquid crystal cell; a pixel TFT 102 for applying a signal voltage to said liquid crystal cell; a signal line 103 for supplying the signal voltage to the liquid crystal cell of each pixel; a buffer capacitance 105; a switching TFT 106 for accumulating an external signal pulse S_{Vi} in a corresponding buffer capacitance 105; a horizontal shift register 107 for pulse driving the switching TFT's 106; a transfer gate 104 for supplying the external S_{Vi} , accumulated in the buffer capacitance 105, to the signal line 103; a vertical shift register 108 for driving the pixel TFT's 102; a resetting signal line 109 connected to a fixed resetting bias source; and a switching TFT for avoiding electrical short-circuiting between the resetting signal line 109 and the recording signal line 103.

Fig. 15 is a timing chart showing an example of the timings of pulses for applying a signal V_{LC} to a pixel in an arbitrary line. Within a horizontal scanning period consisting of an effective scanning period T_E and a blanking period T_B , the application of the resetting signal and the recording of the optical information signal can be executed within said blanking period T_B . The blanking period T_B is divided into a first period T_{B1} for the application of the resetting signal T_{RES} and a second period T_{B2} for the application of the optical information signal V_{IN} . Within said blanking period T_B , two signals, namely the resetting signal V_{RES} and the optical information signal V_{IN} , are transmitted through the signal line 103, and these signals are differently handled by the on-off control of the switch TFT 110. A signal ϕ_{Vi} from the vertical shift register 108 effects on-off control of the pixel TFT, while a signal ϕ_{RES} effects the on-off control of the switching TFT 110, and a signal ϕ_T effects the on-off control of the transfer gate 104.

For example, in a television display of the high definition format, about 2,000 pixels have to be driven per every horizontal line, but a horizontal line can be collectively reset by simultaneously driving all the TFT's by a single pulse in the first period T_{B1} of the blanking period T_B .

By driving an active matrix liquid crystal display device with the circuit configuration and the signal timings explained above, the resetting signal V_{RES} can be supplied to each pixel without passing through the buffer capacitance but merely by charging the parasite capacitance 111 actually associated with the signal line 111, so that a high-speed resetting can be realized.

The timing of resetting is not limited to the case shown in Figs. 15 and 16 in which the resetting signal is given to each pixel or each line immediately before the recording of optical information therein, but can be suitably selected according to the response of the liquid crystal material to be employed. For example, if the response of the liquid crystal material to be employed is slow, it is possible to provide a line with the resetting signal in advance, by a time corresponding to several scanning periods, prior to the recording of optical information therein, thereby giving an ample time for response.

In the embodiment 5 explained above, as the resetting signal is supplied, from an independent resetting voltage source, to the signal line through a path separate from the path for supply of the recording signal voltage to the pixels, the pixel resetting can be achieved with a higher speed in comparison with the conventional configuration in which the resetting signal is supplied through the buffer capacitance in the same manner as the recording signal.

Consequently, there can be provided an active matrix liquid crystal display device capable of high-speed operation, which can be used for constituting a flat display of direct observation type or a projection display, with a high definition. It is also possible to obtain a flat color television of transmissive or reflective type or a projection television, with a high definition, by providing the pixels respectively with different color filters, or by employing a plurality of the liquid crystal devices of the present invention and illuminating said devices with respectively different colored lights.

[Embodiment 6]

Fig. 16 shows a driving circuit for the active matrix liquid crystal device constituting an embodiment 6 of the present invention, wherein shown are a liquid crystal cell 101 represented by a capacitance associated therewith; a pixel TFT 102 for applying a signal voltage to said liquid crystal cell 101; a recording signal line 103; a transfer gate 104; a buffer capacitance 105; a switching TFT 106 for accumulating an external signal pulse in a corresponding buffer capacitance; a horizontal shift register 107 for pulse driving the switching TFT's 106; a vertical shift register 108 for driving the pixel TFT's 102; a gate signal line 110 for driving the pixel TFT's 102 by the output signals of the vertical shift register 108; a resetting line 109 connected to an unrepresented resetting voltage source; and a switching TFT 110 for selectively connecting the recording signal lines 103 with the resetting line 109.

In the following there will be explained, with reference to Fig. 17, the functions of the active matrix liquid crystal device employing the above-explained driving circuit and the TN liquid crystal, in line-sequential drive with signal inversion in every frame.

When image signals of a line are entered in succession from the input terminal 112, they are respectively transferred to the buffer capacitances 105 through the switching TFT's 106 which are turned on by the horizontal shift register 107 driven by the pulses synchronized with the frequency of said image signals. Within so-called blanking period t_b which is after the transfer of the last bit of the line to the buffer capacitance 105 (t_1 in Fig. 17) but before the entry of the image signals of a next line to the input terminal 112 and during which the switching TFT's 116 are turned off, the switching TFT's 110 and the pixel TFT's 102 are simultaneously turned on (t_2) while the transfer gates 104 are turned off, thereby resetting the pixel electrodes from the signal voltages to the pixel resetting voltage V_{RES} . Said resetting voltage V_{RES} is usually selected between the maximum value V_{MAX} of the signal voltage and the inverted value $-V_{MAX}$ thereof, commonly at the middle thereof. Said pixel resetting operation is executed in a part of the blanking period. The resetting period, in which the switching TFT's 110 are turned on ($t_R = t_3 - t_2$), should be at least enough for charging the parasite capacitance C_s of the signal line 103 and the pixel capacitance 101 of the pixel to be reset. In the remaining part of the blanking period, after the switching TFT's 110 are turned off, the transfer gates 104 are turned on (t_4) thereby transferring the signals from the buffer capacitances to the respective pixels, and the pixel TFT's 102 and the transfer gates 104 are turned off before the end of the blanking period (t_b). As a result, each pixel electrode is reset once during the change from the signal voltage of the present to the inverted signal voltage in the next frame, so that the on-state source-drain bias applied to the pixel TFT 102 does not exceed V_{MAX} .

The above-explained timings are shown in Fig. 17, wherein shown are the image signals S_{Vi} of the N-th and (N+1)-th lines; gate input signals ϕ_{RES} , $\phi_{V1} - \phi_{Vn}$ respectively of the switching TFT's 110 and the pixel TFT's 102; the input signal ϕ_T of the transfer gates 104; and the signal voltages of the pixels of the N-th line (solid line) and the (N+1)-th line (broken line). As will be apparent from the charts, the pixel electrode is maintained at the resetting voltage V_{RES} in the course of change from the signal voltage to the next inverted signal voltage, whereby the on-state source-drain bias applied to the pixel TFT is alleviated.

In the following there is considered the variation in the signal voltage under the above-explained situation. The period t_R , in which the pixel voltage is maintained at the set level, is in the order of microseconds less than the blanking period, and the liquid crystal molecules do not respond to such voltage variation within such short period. In this state, with the resetting potential V_{RES} , the effective voltage V_{rms} actually applied to the liquid crystal can be represented as follows, based on the foregoing equation (1):

$$V_{rms} = \sqrt{\frac{1}{t_F} \int_0^{t_F} (V_{LC}(t) - V_{COM})^2 dt + \frac{1}{t_F} \int_0^{t_R} (V_{LC}(t) - V_{COM})^2 dt} \quad (12)$$

Consequently the curve representing the relationship between the transmittance (T) and the effective voltage (V_{rms}) is displaced by the contribution of the resetting voltage V_{RES} , but the image is not influenced if t_R is sufficiently negligibly with respect to a frame period. For example, in the high definition television image signal, a frame period is about 33 msec, and a blanking period therein is about 3 μ sec. In said blanking period, the period required for pixel resetting is about 1 μ sec. Consequently the pixel electrodes are maintained at the resetting potential V_{RES} for 2/33000 of a frame period, but is maintained at the signal voltage V_{LC} for 32998/33000 of the frame period, so that the influence to the image is extremely small.

Also as explained above, the curve representing the relationship between the transmittance T and the effective voltage V_{rms} is displaced by the contribution of V_{RES} , but the effective voltage V_{rms} is uniquely deter-

mined by a given value of V_{LC} , as long as the resetting voltage V_{RES} and the resetting time t_R are constant. Consequently the characteristics of the display device may be determined, based on thus displaced curve. It is also possible to cancel said displacement by the regulation of the original signal voltage V_{LC} .

Since the bias voltage applied to the pixel TFT's is reduced as explained above, the vertically streaking smear, resulting from the swing of the signal voltage of each pixel, under the influence of signals in other pixels connected to a same signal line, is eliminated and the image quality is therefore improved.

[Embodiment 7]

Fig. 18 is a timing chart of an embodiment 7, utilizing also the circuit shown in Fig. 16. In this embodiment 7, after the switching TFT's 106 are turned off (t_1) upon completion of the image signals to the buffer capacitance 105, the switching TFT's 110 and the pixel TFT's are simultaneously turned on (t_2) while the transfer gates 104 are turned off, thereby resetting the pixel electrodes from the signal voltages to the pixel resetting voltage. Then the switching TFT's 110 are turned off (t_3) while the pixel TFT's 102 are turned on, and the transfer gates 104 are turned on (t_4) to transfer the signals from the buffer capacitances 105 to the respective pixels 101. The above-explained operations are same as those in the embodiment 1. However, when the pixel TFT's 102 are turned off (t_5) after the signal transfer to the pixels 101, the transfer gates 104 are not turned off simultaneously but maintained in on-state, and the switching TFT's 110 are again turned on (t_6), thereby resetting the buffer capacitances 105 also to the reset voltage V_{RES} .

In the foregoing embodiment 6, signals inverted every frame are supplied from the input terminal 112 to the buffer capacitances 105 through the switching TFT's 106, and, in such signal supply, an on-state source-drain bias voltage of $2V_{MAX}$ at maximum is applied to said switching TFT's in a similar manner as in the pixel TFT's 102 in the conventional configuration. However, with the timings shown in Fig. 18, the potential of the buffer capacitances 105 is reset in the course of change from the signal voltages to the next inverted signal voltages, so that the on-state source-drain voltage resistance can be reduced not only in the pixel TFT's 102 but also in the switching TFT's 110. The on-state of the switching TFT's 110 required for the resetting of the buffer capacitances 105 should be at least enough for charging the parasite capacitances of the signal lines 103 and the buffer capacitances 105. The switching TFT's 110 and the transfer gates 104 are turned off before the end of the blanking period. As a result the on-state source-drain bias applied to the pixel TFT's 106 is also alleviated.

In Fig. 18 there are shown the image signals S_{Vi} of the N-th and (N+1)-th lines; the gate input signals ϕ_{RES} , $\phi_{M1} - \phi_{Mn}$ respectively of the switching TFT's 106 and the pixel TFT's 102; the transfer gate input signal ϕ_T ; and the signal voltages of the pixels in the N-th line (solid line) and in the (N+1)-th line (broken line). As will be apparent from these charts, the pixel electrode is maintained-once at the resetting voltage in the course of change from the signal voltage to the next inverted signal voltage, whereby the on-state source-drain bias is alleviated not only the pixel TFT's 102 but also in the switching TFT's 110.

[Embodiment 8]

Fig. 20 is a timing chart of an embodiment 8 also utilizing the circuit shown in Fig. 16. In this embodiment, in the blanking period t_B after the switching TFT's 106 are turned off (t_1) upon completion of transfer of the image signals of a line to the buffer capacitances 105, the pixel TFT's 102 are turned on (t_2) while the transfer gates are maintained turned off. The switching TFT's 110 are already turned on from the horizontal scanning period, thereby resetting the pixel electrodes from the signal voltages to the resetting voltage V_{RES} . Said resetting voltage V_{RES} is selected between the maximum value V_{MAX} of the signal voltage and the inverted voltage $-V_{MAX}$ thereof, normally at the middle thereof. Said pixel resetting operation is executed in a part of the blanking period. The on-state period of the switching TFT's 110 should be at least enough for charging the parasite capacitances C_S of the signal lines 103 and the pixel capacitances 101 to be reset. In the remaining part of the blanking period after the switching TFT's 110 are turned off (t_3), the transfer gates 104 are turned on while the pixel TFT's 102 are maintained turned on (t_4), thereby transferring the signals from the buffer capacitances 105 to the respective pixels 101. After said signal transfer, the pixel TFT's 102 are turned off (t_5) while the transfer gates 104 are maintained in the on-state, and the switching TFT's 110 are again turned on (t_6) thereby resetting the buffer capacitances 105 also to the resetting potential. Then the transfer gates 104 are turned off (t_7) before the end of the blanking period. The switching TFT's 110 are still maintained in the on-state during a horizontal scanning period, in order to maintain the signal lines 103 at a constant voltage.

In Fig. 19, there are shown the image signals S_{Vi} of the N-th and (N+1)-th lines; the gate input signals ϕ_{RES} , $\phi_{M1} - \phi_{Mn}$ respectively of the switching TFT's 110 and the pixel TFT's 102; the input signal ϕ_T of the transfer gates; and the signal voltages of the pixels of the N-th line (solid line) and the (N+1)-th line (broken line). As

will be apparent from these charts, the pixel electrodes are maintained once at the resetting voltage in the course of change from the signal voltages to the next inverted signal voltages, so that the on-state source-drain bias is alleviated not only in the pixel TFT's 102 but also in the switching TFT's 106.

Thus the present embodiment not only reduces the requirements for the voltage resistance of TFT's but also suppresses the aforementioned variation in the signal voltage.

More specifically, the signal voltage in each pixel is no longer influenced by those in other pixels connected to the same signal line, whereby the vertically streaking smear can be eliminated and the image quality is therefore improved.

[Embodiment 9]

Fig. 20 is a circuit diagram of a driving circuit for the active matrix liquid crystal device constituting an embodiment 9 of the present invention. The circuit shown in Fig. 20 is obtained by adding, to the circuit shown in Fig. 16, a second resetting circuit for resetting the buffer capacitances 105. Said second resetting circuit is similar to the aforementioned resetting circuit for resetting the pixel potential, and is composed of a resetting line 512 connected to a buffer capacitance resetting power source, and switching TFT's 513 for connecting said resetting line 512 selectively with the recording signal lines 103.

In the following there will be explained, with reference to Fig. 21, the functions of an active matrix liquid crystal device employing TN liquid crystal, in a line-sequential drive with inversion of polarity in every frame.

When the image signals of a line are entered in succession from the input terminal 112, said signals are transferred to the buffer capacitances 105 by the switching TFT's 106 turned on by the horizontal shift register 107 which is driven by the pulses synchronized with the frequency of said signals. In the so-called blanking period t_B which is after the transfer of the signal of the last bit of said line into the buffer capacitance (t_1 in Fig. 21) but prior to the entry of the image signals of a next line into the input terminal 112, the pixel TFT's 102 are turned on (t_2). The switching TFT's 110 are already in the on-state from the preceding horizontal scanning period, whereby the pixel electrodes are reset from the signal voltages to the pixel resetting voltage V_{RES} . Said resetting voltage is selected between the maximum value V_{MAX} of the signal voltage and the inverted value $-V_{MAX}$ thereof, generally at the middle thereof. Said pixel resetting operation is executed in a part of the blanking period. The on-period of the switching TFT 110 should be at least enough for charging the parasite capacitance C_s of the signal line 103 and the pixel capacitance 101 of the pixel to be reset. In the remaining part of the blanking period after the switching TFT's 110 are turned off (t_3), the transfer gates 104 are turned on (t_4) to transfer the signals from the buffer capacitances 105 to the respective pixels. After said signal transfer, the pixel TFT's 102 and the transfer gates 104 are turned off (t_5 , t_7). Subsequently the switching TFT's 513 are turned on (t_6), thereby resetting the buffer capacitances 105 also. Then, after the TFT's 513 are turned off (t_8), the switching TFT's 110 are turned on (t_{10}).

In this embodiment, since the resetting of the pixel 101 and the signal line 103 is executed by the switching TFT 110 while the resetting of the accumulating capacitance 105 is executed by the separate TFT 513, so that the loads on these TFT's can be alleviated and the resetting operation can be achieved with a higher speed.

Fig. 21 shows the timings of functions of the present embodiment. In Fig. 21 there are shown the image signals S_{Vi} of the N-th and (N+1)-th lines; the gate input signals ϕ_{RES} , ϕ_{Vi} - ϕ_{Vn} respectively of the switching TFT 110 and the pixel TFT 102; the input signal ϕ_T of the transfer gate 104; the pixel signals voltages V_{PE} of the N-th line (solid line) and the (N+1)-th line (broken line); and the gate input signal ϕ_{CTR} of the switching TFT 513. As will be apparent from these charts, the pixel electrode is once maintained at the resetting voltage in the course of change from the signal voltage to the next inverted signal voltage, whereby the on-state source-drain bias is alleviated not only in the pixel TFT 102 but also in the switching TFT 106.

[Embodiment 10]

Fig. 22 shows the function timings constituting an embodiment 10 utilizing the circuit shown in Fig. 20. Said embodiment 10 on the circuit shown in Fig. 20 corresponds to the functions shown in Fig. 3 on the circuit shown in Fig. 1, and the resetting operation of the buffer capacitances 105 is effected by the switching TFT's 513 instead of the switching TFT 110 in case of Fig. 18.

In the embodiment shown in Figs. 20 and 22, when the image signals of a line are entered in succession from the input terminal 112, said signals are transferred to the buffer capacitances 105 by the switching TFT's 106 turned on by the horizontal shift register 107 which is driven by pulses synchronized with the frequency of said image signals. In the so-called blanking period t_B which is after the transfer of the signal of the last bit of said line into the buffer capacitance (t_1) but before the entry of the image signals of a next line into the input terminal 112, the switching TFT's 110 and the pixel TFT's 102 are simultaneously turned on while the transfer

gates 104 are maintained in the off-state (t_2), whereby the pixel electrodes are reset from the signal voltages to the pixel resetting voltage V_{RES} . Then the switching TFT's 110 are turned off (t_3) while the pixel TFT's 102 are maintained in the on-state, and the transfer gates 104 are turned on (t_4), thereby transferring the signals from the buffer capacitances 105 to the respective pixels 101. After said signal transfer to the pixels 101, the pixel TFT's 102 are turned off (t_5), and the switching TFT's 513 are turned on (t_6). Thus the buffer capacitances 105 and the parasite capacitances 113 are reset to the potential of the buffer capacitances, which is equal to the potential of the resetting line 512. Subsequently the transfer gates 104 and the switching TFT's 513 are turned off (t_7 , t_8) within the remaining part of the blanking period t_b .

In the present embodiment, as in the embodiment 9, the loads on the TFT's for resetting the pixel capacitance 101 and the buffer capacitance 105 can be alleviated, so that the resetting operation can be achieved with a higher speed. Also the on-state source-drain bias can be reduced in the pixel TFT's 102 and in the switching TFT's 106.

[Embodiment 11]

In the foregoing embodiments 6 to 10, the active matrix is driven by a line-sequential driving method for every horizontal line, but similar effects can also be attained in a pixel-sequential drive.

Fig. 23 shows a driving circuit for the sequential-drive active matrix liquid crystal device of the present embodiment, wherein shown are a capacitance 101 of a liquid crystal cell; a pixel TFT 102 for applying a signal voltage to said liquid crystal cell 101; a signal line 103; a switching TFT 104 for accumulating an external signal pulse in a corresponding liquid crystal cell capacitance; a first horizontal shift register 107 for pulse driving the switching TFT's 104; a vertical shift register 108 for driving the pixel TFT's; a resetting line 109 connected to a pixel resetting source; a switching TFT 110 for selectively connecting the resetting line 109 with the recording signal line 103; and a second horizontal shift register 810 for driving the switching TFT's 110.

In the following there will be explained, with reference to Fig. 24, the functions of the circuit shown in Fig. 23.

At first the pixel TFT's 102 of a line selected by the vertical shift register 108 are turned on (t_{11} in Fig. 24). Then the second shift register 810 in succession turns on the switching TFT's 110 (t_{12}), thereby resetting the pixels 101 to the resetting potential V_{RES} . After said resetting the TFT's 110 are turned off (t_{13}), and the image signals of a line are entered in succession from the input terminal 112 and are transferred, in succession, to all the pixels of a horizontal line through the switching TFT's 104, which are turned on by the first horizontal shift register 107 driven by pulses synchronized with the frequency of said image signals ($t_{14} - t_{15}$).

Fig. 25 shows the function timings of the present embodiment. In Fig. 25 there are shown the image signals S_{Vi} of the N-th and (N+1)-th lines; the gate input signals $\phi_{V1} - \phi_{Vn}$, $\phi_{HR1} - \phi_{HRm}$, $\phi_{HT1} - \phi_{HTm}$ respectively of the pixel TFT's 102, switching TFT's 110 and transfer gates 104; and the pixel signal voltages V_{PE} of the N-th line (solid line) and the (N+1)-th line (broken line). As will be apparent from these charts, the pixel electrode is once maintained at the resetting voltage in the course of change from the signal voltage to the next inverted signal voltage, whereby the on-state source-drain bias applied to the pixel TFT's 102 is alleviated.

The embodiments 6 to 11 explained above can provide an active matrix liquid crystal display device capable of achieving a high definition and a high-speed drive without a large burden on the display device structure, and an active matrix liquid crystal display employing such device. Thus, there can be formed a flat display for direct observation or a projection display, of a high definition. Naturally it is also possible to construct a color television or a projection color television, by providing the pixels with different color filters, or by employing a plurality of the liquid crystal device adopting the driving method of the present invention and illuminating said devices with different colored lights.

Fig. 25 is a block diagram of an information signal processing system including the liquid crystal device of the present invention, wherein provided are a liquid crystal device 1 for displaying an image; a drive control circuit 2 for controlling the drive of said liquid crystal device and releasing the aforementioned resetting signal ϕ_{RES} , resetting reference voltage V_{RES} , transfer signal ϕ_T , image signal S_{Vi} , and clock signal ϕ_{CLK} for driving the shift registers; an image input circuit 3 for reading image information from an original ORL bearing said image information by means of a photoelectric converting device 7; an information recording circuit 4 for recording the information on a recording medium RCM by means of a recording head 8, which can be an ink jet recording head or a thermal head in case said medium RCM is paper or a plastic sheet, or can be a magnetic head or an optical head in case said medium RCM is a magnetic tape, an optical disk or a magnetic disk; a communication circuit 5 for effecting communication with the outside through a channel NT; and a control circuit 6 for controlling the above-mentioned circuits, and provided with a known central processing unit CPU.

Fig. 26 illustrates a liquid crystal device, wherein included are a main frame 10; semiconductor integrated circuits 11 including the vertical shift register 108; semiconductor integrated circuits 12 including the horizontal

shift register, buffer circuits and resetting circuits; and a liquid crystal display unit 13 containing a layer of a liquid crystal material between a pair of substrates, one of which bears matrix lines 103, 111, active elements 15, and individual pixel electrodes 14.

As explained in the foregoing, the present invention can provide a liquid crystal device capable of effecting high-speed drive and suppressing the smear in inexpensive manner.

Claims

1. A liquid crystal device of active matrix type including a layer of a liquid crystal material and a plurality of unit cells each provided with an active element, comprising:
 - a circuit for maintaining signal lines, for supplying signals for determining the optical state of the liquid crystal material, at a reference potential during a period, other than a period in which said signals are supplied to said unit cells.
2. A device according to claim 1, comprising:
 - a reference voltage supply line, for supplying a reference voltage for maintaining said signal lines at the reference potential, said supply line being separate from the signal supply line for supplying said signals.
3. A device of active matrix type including a layer of a liquid crystal material and a plurality of unit cells each provided with an active element, comprising:
 - a circuit for supplying said unit cells with time-sequential signals for determining the optical state of the liquid crystal material, said circuit being adapted to maintain said unit cells at a reference potential after the supply of first signals to said unit cells but prior to the supply of succeeding second signals.
4. A device according to claim 3, comprising:
 - a reference voltage supply line for supplying a reference voltage for maintaining said unit cells at the reference potential, said supply line being separate from a signal supply line for supplying said time-sequential signals.
5. A device of active matrix type including a layer of a liquid crystal material having at least two stable states, and a plurality of unit cells each provided with an active element, comprising:
 - a circuit for supplying time-sequential signals, for determining the optical state of the liquid crystal material, from a common signal line to said unit cells;
 - a circuit for maintaining said unit cells at a reference potential, after the supply of first signals among said time-sequential signals to said unit cells but prior to the supply of second signals, succeeding to said first signals, to said unit cells; and
 - a reference voltage supply line for supplying a reference voltage for maintaining said unit cells at the reference voltage, said supply line being separate from said common signal line.
6. A device according to claim 5, wherein said circuits include a thin film transistor.
7. A device according to claims 1, 3 or 5, wherein said circuit, said circuit, or said circuit first mentioned, is adapted to supply the unit cells with said signals in time-sequential manner.
8. A device according to claims 1, 3 or 5, wherein said circuit, said circuit, or said circuit first mentioned, is adapted to supply each line connected to plural unit cells with said signals in time-sequential manner.
9. A device according to claims 1, 3 or 5, wherein the reference voltage for maintaining said signal lines at the reference potential is a voltage of about the middle of the maximum and minimum voltages of said signals.
10. A device according to claims 1, 3 or 5, wherein the reference voltage for maintaining said signal lines at the reference potential is a voltage equal to the maximum or minimum voltage of said signals.
11. A device according to claims 1, 3 or 5, wherein said signal lines are provided with accumulating capacitances for temporarily storing said signals, and between each of said accumulating capacitances and each of said active elements there is provided a switch for electrically connecting said capacitance and said

active element.

12. A device according to claims 1, 3 or 5, wherein the reference voltage supply line, for supplying the reference voltage for maintaining said signal lines at the reference potential, is connected to a power source provided in another circuit.
13. A device according to claims 1, 3 or 5, wherein said liquid crystal material is nematic liquid crystal.
14. A device according to claims 1, 3 or 5, wherein said liquid crystal material is ferroelectric liquid crystal.
15. A device according to claim 5, wherein said liquid crystal material is smectic liquid crystal.
16. A driving method for a liquid crystal device of active matrix type including a layer of a liquid crystal material and a plurality of unit cells each provided with an active element, comprising:
 - a step of maintaining signal lines for supplying signals, for determining the optical state of the liquid crystal material, at a reference potential during a period other than a period in which said signals are supplied to said unit cells.
17. A driving method for a liquid crystal device of active matrix type including a layer of liquid crystal material and a plurality of unit cells each provided with active elements, comprising:
 - a step of maintaining said unit cells at a reference potential, after the supply, to said unit cells, of first signals among time-sequential signals for determining the optical state of the liquid crystal material but prior to the supply, to said unit cells, of second signals succeeding to said first signals.
18. A driving method for a liquid crystal device of active matrix type including a layer of a liquid crystal material having at least two stable states, and a plurality of unit cells each provided with an active element, comprising steps of:
 - supplying time-sequential signals for determining the optical state of the liquid crystal material from a common signal line to said unit cells; and
 - connecting said unit cells to a reference voltage supply line separate from said common signal line, after the supply, to said unit cells, of first signals among said time-sequential signals but prior to the supply, to said unit cells, of second signals succeeding to said first signals, thereby maintaining said unit cells at a reference potential.
19. An apparatus comprising a liquid crystal device according to claims 1, 3 or 5, and a circuit for generating instructions for controlling the drive of said device.
20. An apparatus comprising a circuit for generating instructions for executing the driving method according to any of claims 16 to 18.

FIG. 1
PRIOR ART




FIG. 2
PRIOR ART




FIG. 3




FIG. 4A
PRIOR ART




FIG. 4B
PRIOR ART




FIG. 5
PRIOR ART




FIG. 6
PRIOR ART




FIG. 7




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 26





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 31 0121

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	EP-A-0 284 134 (PHILIPS) * column 6, line 1 - line 28; figures 3,4 *	1,3,7,8, 14,16, 17,20	G09G3/36
D	& US-A-4 840 462 ---		
A	EP-A-0 313 876 (IBM) * abstract; figures 4,7 * * page 3, line 57 - page 6, line 23 * ---	1,3,5, 16-18	
A	PROCEEDINGS OF THE SID. vol. 32, no. 4, 1991, LOS ANGELES US pages 331 - 337 H. HORI 'Key Issues Regarding High-Information-Content TFT-LCDs for Data Graphics' * the whole document * ---	1,3,5, 16-18	
A	IEEE TRANSACTIONS ON ELECTRON DEVICES vol. 36, no. 9I, September 1989, NEW YORK US pages 1938 - 1942 W. HOWARD ET AL. 'Eliminating Crosstalk in Thin-Film Transistor Liquid-Crystal Displays' * page 1941, paragraph IIIB; figure 7 * -----	1,3,5, 16-18	TECHNICAL FIELDS SEARCHED (Int. Cl.5) G09G
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 08 FEBRUARY 1993	Examiner SAAM C.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (01.82) (P0401)